

Chopped Strand for BMC

ECS402B

Identification

Example : ECS402B-3-H
ECS : E-glass Chopped strands
Sizing code : 402B
Chopped length (mm) : 3
Filament diameter : 10



Product Description

This kind is specially designed for BMC processing, showing better mechanical properties. Applied in requirements on fire retardant, for example, car ashtray , wiper motor ,etc..

Product Benefits

- Particles distributions
- Good flow ability
- Good Compatibility and reactivity with basic resin
- Excellent mechanical properties and higher strength

Technical Characteristics


Compatible Resin	Diameter (μm)	Moisture Content (%)	Loss on Ignition (%)	Bulk Density (g/ cm3)
/	ISO 1888	ISO 3344	ISO 1887	ISO 15100
Phenolic Resin	±1	≤0.1	□0.8±0.1	0.7±0.15

Product code	Glass Type	Filament diameter[μm]	Chopped length [mm]
ECS402B	ECT	10	1.7、3

Packing

Package Method	Package weight [kg]	Quantity	Pallet size [mm] Length*width*height
Super sack bag	1000	1 pallet	1140*1140*1100
Poly-plastic film bag	25	40 bags	850*500*120

Pallets illustration



Note: Products can be packed according to the customer's request.

Storage

- If no special requirements, it should be stored in cool and dry place .The recommended temperature range is 10-30℃ ,humidity should be 50 -75%.
- The product should be always kept package encapsulation before use.
- Pallet stacking height should not over 1 layer.



ISO 9001



ISO 14001



OHSAS 18001