

Chopped Strand for BMC

ECS404

Identification

Example : ECS404-6-L
ECS : E-glass Chopped strands
Sizing code : 404
Chopped length (mm) : 6
Filament diameter : 13.7



Product Description

This kind is specially designed for BMC processing. Applied in electronic components, construction pipeline joint ,etc

Product Benefits

- Good flowability
- Good Compatibility with basic resin
- Excellent GFRP properties

Technical Characteristics


Compatible Resin	Diameter (μm)	Moisture Content (%)	Loss on Ignition (%)	Bulk Density (g/ cm ³)
/	ISO 1888	ISO 3344	ISO 1887	ISO 15100
UP、VE	±1	≤0.1	1.65±0.2	±0.15

Product code	Glass Type	Filament diameter[μm]	Chopped length [mm]
ECS404	ECT	13.7	6、12、24、48

Packing

Package Method	Package weight [kg]	Quantity	Pallet size [mm] Length*width*height
Super sack bag	1000	1 pallet	1140*1140*1100
Poly-plastic film bag	25	40 bags	850*500*120

Pallets illustration



Note: Products can be packed according to the customer's request.

Storage

- If no special requirements, it should be stored in cool and dry place .The recommended temperature range is 10-30℃ ,humidity should be 50 -75%.
- The product should be always kept package encapsulation before use.
- Pallet stacking height should not over 1 layer.



FIBERGLASS